

Sub series



Our subwoofer models bring true Dynaudio sound quality to any home cinema or sub-sat music system. The Sub 250 II and Sub 600 perfectly complement any Dynaudio loudspeaker, delivering fast, deep, precise and natural bass.

DYNAUDIO



Sub 600



Sub 250 II

Sub series

Data

	Sub 600	Sub 250 II
Analog inputs	1 x RCA LFE, 2 x RCA Stereo	1 x RCA LFE, 2 x RCA Stereo
Analog outputs	1 x RCA slave out, 2 x RCA SAT out	1 x RCA slave out, 2 x RCA SAT out
Frequency response (+/- 3 dB)	18Hz – 250Hz	29Hz – 250Hz
Box principle	Sealed	Sealed
High-pass filter	Flat / 60Hz / 80Hz	Flat / 60Hz / 80Hz
Low-pass filter	50Hz-150Hz	50Hz-150Hz
Phase adjustment	0/180 degrees	0/180 degrees
Woofer	30cm MSP	24cm MSP
Amplifier power	300W	200W
AC power input	100-240V 50/60Hz	100-240V 50/60Hz
Power consumption (standby)	< 0.5W	< 0.5W
Power consumption (max)	325W	325W
Weight	21kg / 46lb	7.2kg / 15lb
Dimensions (W x H x D)	350 x 370 x 420mm 13.8 x 14.6 x 16.5in	266 x 271 x 308mm 10.5 x 10.7 x 12.2in
Dimensions with feet/grille (W x H x D)	350 x 370 x 435mm 13.8 x 14.6 x 17in	266 x 271 x 323mm 10.5 x 10.7 x 12.7in

Sub 600 finishes/grilles: Black Ash Satin/Black, Black Piano Lacquer/Black, Rosewood Satin/Black, Walnut Satin/Black and White Piano Lacquer/Black

Sub 250 II finishes/grilles: Black Satin/Black, Rosewood Dark Satin/Black, Walnut Satin/Black and White Satin/Black



Sub
Deep bass with authentic Dynaudio sound quality

Sub
Designed,
engineered
and assembled
in Denmark

Learn more, get the latest tips and tricks and read our reviews on
[dynaudio.com](https://www.dynaudio.com) and facebook.com/dynaudiogroup

DYNAUDIO

Dynaudio A/S
Sverigesvej 15
8660 Skanderborg
Denmark

www.dynaudio.com

Product Series Insert, Sub
Item no. 45538210A

All text and image copyrights reserved
Subject to change without notice